

TRAFFIC ARRANGEMENTS – LOADING @ PHALABORWA GYPSUM

The recent heavy rains (800mm+) have had a severe impact on our loading operations. As our loading area is located inside a dam, we were unable to divert the rainwater away. We are currently draining the water into a holding pond to prevent contamination of the Selati River.

An alternative loading area has been prepared; however, we need to impose the following rules to ensure everyone's safety:

Please share the following rules and regulations with your drivers coming to load:

- ✓ Drivers must report to **Bosveld Reception**, obtain a permit, proceed to the **weighbridge for empty weighing**, and then continue to the **stockpile near the loading area**.
 - Loading will be slow due to limited dry space inside the dam to prepare product stockpile, and load trucks.
 - To prevent congestion on site and possible damage to equipment, **only two trucks will be allowed inside the loading area at a time**.
 - Trucks next in line must wait in the **designated area just outside the loading area**.
 - Only proceed into the loading area when a truck has exited (**one out, one in**), unless instructed otherwise by a **Phalaborwa Gypsum staff member**.
 - After loading, please leave the loading area as soon as possible to allow access for the next truck.
- ✓ Proceed to the weighbridge to determine **loaded tonnage**. If necessary, return to the load adjusting area, obtain final weight, collect load documentation, proceed to the tarping area, and then depart.

